

View Online at <https://aerobasegroup.com/nsn/5340-01-107-3196>

**First Leg Length:**

Between 2.080 inches and 2.320 inches

**Second Leg Length:**

2.600 inches

**Second Leg Width:**

3.000 inches

**Second Leg End Width:**

2.240 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.750 inches

**Second Leg Slot Length:**

1.000 inches

**Second Leg Slot Width:**

Between 0.405 inches and 0.465 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

3.000 inches

**First Leg End Width:**

2.240 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

No hole

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 42.0 degrees and 48.0 degrees

**First Leg Chamfer Angle:**

45.0 degrees

**Second Leg Chamfer Angle:**

45.0 degrees

**Special Features:**

Qstiffener p/n 12297219-2 added to center of bracket, width is 0.240in., lgth is 4.92in., height is 0.600in., 1st end coated with plastic, plastisol, type 1, class 2, spec mil-p-20689, .03 to.09 thick, 2.08 to 2.32in. Along lgth

**Material:**

Aluminum alloy 5083

**Material Specification:**

Qq-a-250/6 federal specification single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0