

View Online at <https://aerobasegroup.com/nsn/5340-01-107-3196>

First Leg Length:

Between 2.080 inches and 2.320 inches

Second Leg Length:

2.600 inches

Second Leg Width:

3.000 inches

Second Leg End Width:

2.240 inches

Second Leg Distance Between Hole Centers Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

Second Leg Slot Length:

1.000 inches

Second Leg Slot Width:

Between 0.405 inches and 0.465 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

3.000 inches

First Leg End Width:

2.240 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 42.0 degrees and 48.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

Qstiffener p/n 12297219-2 added to center of bracket, width is 0.240in., lgth is 4.92in., height is 0.600in., 1st end coated with plastic, plastisol, type 1, class 2, spec mil-p-20689, .03 to .09 thick, 2.08 to 2.32in. Along lgth

Material:

Aluminum alloy 5083

Material Specification:

Qq-a-250/6 federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0