

View Online at <https://aerobasegroup.com/nsn/5340-01-108-9073>

First Leg Length:

4.030 inches

Second Leg Length:

4.030 inches

End Application:

2350-01-091-5405 carrier mlrs

Second Leg Width:

10.000 inches

First Leg Slot Length:

Between 0.310 inches and 0.336 inches

First Leg Slot Width:

Between 0.470 inches and 0.530 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

4.500 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

4.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.380 inches

Second Leg Slot Length:

Between 0.430 inches and 0.460 inches

Second Leg Slot Width:

Between 0.560 inches and 0.680 inches

First Leg Thickness:

0.190 inches

Second Leg Thickness:

0.190 inches

Center Section Height:

11.250 inches

Center Section Width:

10.120 inches

Center Section Thickness:

0.190 inches

First Leg Width:

6.220 inches

First Leg Distance Between Hole Centers Along Width:

4.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

0.392 inches

First Leg Style:

Extended flat

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Extended flat

Second Leg Hole Arrangement Style:

3 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Aluminum alloy 5083

Material Specification:

Qq-a-250/6 federal specification single material response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0