

View Online at <https://aerobasegroup.com/nsn/5340-01-108-9266>

First Leg Length:

2.500 inches

Second Leg Length:

3.000 inches

End Application:

M2/1fv and m3/cfv configuration

Second Leg Width:

2.000 inches

Second Leg End Width:

1.000 inches

First Leg Slot Length:

0.625 inches

First Leg Slot Width:

0.308 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.190 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

Second Leg Slot Length:

1.000 inches

Second Leg Slot Width:

0.430 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

2.000 inches

First Leg End Width:

1.500 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance Between Hole Centers Along Length:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.430 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.310 radians

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Second Leg Slot Offset Angle:

0.3 radians

Material:

Aluminum alloy 5083

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0