

View Online at <https://aerobasegroup.com/nsn/5340-01-109-4905>

Fabrication Method (non-core):

Cast

Mounting Hole Type:

Countersunk

First Leg Length:

1.625 inches

Second Leg Length:

1.750 inches

Second Leg Width:

1.500 inches

Second Leg Corner Radius:

0.250 inches

First Leg Hole Diameter:

0.204 inches

Second Leg Hole Diameter:

Between 0.406 inches and 0.422 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.719 inches

First Leg Thickness:

0.281 inches

Second Leg Thickness:

0.875 inches

First Leg Width:

2.500 inches

First Leg Corner Radius:

0.312 inches

First Leg Distance Between Upper Hole Centers Along Width:

1.875 inches

First Leg Distance Between Hole Centers Along Length:

1.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.875 inches

First Leg Distance From Edge To Hole Center Along Width:

0.312 inches

First Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Offset Angle:

65.0 degrees

Special Features:

Second leg hole has bushing 0.375-24nf-2b rh thread

Material:

Aluminum alloy 356.0 and steel comp 1025

Surface Treatment:

Enamel lusterless

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0