

View Online at <https://aerobasegroup.com/nsn/5340-01-109-4905>

**Fabrication Method (non-core):**

Cast

**Mounting Hole Type:**

Countersunk

**First Leg Length:**

1.625 inches

**Second Leg Length:**

1.750 inches

**Second Leg Width:**

1.500 inches

**Second Leg Corner Radius:**

0.250 inches

**First Leg Hole Diameter:**

0.204 inches

**Second Leg Hole Diameter:**

Between 0.406 inches and 0.422 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.719 inches

**First Leg Thickness:**

0.281 inches

**Second Leg Thickness:**

0.875 inches

**First Leg Width:**

2.500 inches

**First Leg Corner Radius:**

0.312 inches

**First Leg Distance Between Upper Hole Centers Along Width:**

1.875 inches

**First Leg Distance Between Hole Centers Along Length:**

1.000 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

1.875 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.312 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.312 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Offset Angle:**

65.0 degrees

**Special Features:**

Second leg hole has bushing 0.375-24nf-2b rh thread

**Material:**

Aluminum alloy 356.0 and steel comp 1025

**Surface Treatment:**

Enamel lusterless

**Style Designator:**

Offset angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0