

View Online at <https://aerobasegroup.com/nsn/5340-01-109-6329>

Mounting Hole Type:

Plain

First Leg Length:

1.120 inches

Second Leg Length:

1.880 inches

Second Leg Width:

27.810 inches

Second Leg Corner Radius:

0.250 inches

First Leg Slot Length:

0.343 inches

First Leg Slot Width:

Between 0.209 inches and 0.229 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

3.422 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

3.422 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.220 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

Second Leg Slot Length:

0.343 inches

Second Leg Slot Width:

Between 0.209 inches and 0.229 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

27.810 inches

First Leg End Width:

27.376 inches

First Leg Distance Between First And Second Hole Centers Along Width:

2.845 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

5.125 inches

First Leg Distance From Edge To Hole Center Along Width:

0.810 inches

First Leg Distance From Edge To Hole Center Along Length:

0.430 inches

First Leg Distance Between Third And Fourth Hole Centers Along Width:

5.125 inches

First Leg Style:

Chamfered ends

Second Leg Style:

Corner radius

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Err Default:

Err default

First Leg Chamfer Angle:

45.0 degrees

Material:

Aluminum alloy 6063

Material Specification:

Qq-a-200/9, t52 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response or mil-c-5541, cl 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.