
NSN 5340-01-111-2843

Angle Bracket - Page 1 of 2



Fabrication Method (non-core):

Any acceptable

Mounting Hole Type:

Plain

## First Leg Length:

0.750 inches

#### Second Leg Length:

0.910 inches

#### Second Leg Width:

1.000 inches

### Second Leg Corner Radius:

0.310 inches

#### First Leg Hole Diameter:

Between 0.129 inches and 0.134 inches

### Second Leg Hole Diameter:

### Between 0.263 inches and 0.266 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

## Second Leg Distance From Edge To Hole Center Along Length:

0.310 inches

## First Leg Thickness:

0.064 inches

### Second Leg Thickness:

0.064 inches

### First Leg Width:

1.000 inches

### First Leg Corner Radius:

0.250 inches

### First Leg Distance Between Hole Centers Along Width:

0.500 inches

# First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

# First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

# First Leg Style:

Corner radius

# First Leg Hole Arrangement Style:

Two holes

# Second Leg Style:

Corner radius

# Second Leg Hole Arrangement Style:

One hole



# NSN 5340-01-111-2843

Angle Bracket - Page 2 of 2



# Second Leg Relationship To First Leg:

Not identical

# First Leg Angle:

90.0 degrees

# Special Features:

One 0.094 in. Diameter lockwire hole and inverted clinch nut installation in second hole

## Material:

Aluminum alloy 2024

## Material Specification:

Qq-a-250/5, t72 or t81 federal specification single material response

## Surface Treatment:

Chromate zinc

## Style Designator:

Angle

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A042a0