

View Online at <https://aerobasegroup.com/nsn/5340-01-112-1596>

**Fabrication Method (non-core):**

Welded

**First Leg Length:**

1.380 inches

**Second Leg Length:**

1.500 inches

**Second Leg Width:**

3.250 inches

**Second Leg End Width:**

2.750 inches

**First Leg Slot Length:**

0.680 inches

**First Leg Slot Width:**

0.406 inches

**Second Leg Hole Diameter:**

Between 0.688 inches and 0.719 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.625 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

3.250 inches

**First Leg End Width:**

2.750 inches

**First Leg Distance Between Hole Centers Along Width:**

2.250 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.535 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Second leg hole has keyway 0.186 lg x 0.156 w parallel to width lh

**Material:**

Aluminum alloy 5086 or aluminum alloy 5083

**Material Specification:**

Qq-a-250/7 al 5086-h32 federal specification 1st material response or qq-a-250/6 al 5083-h323 federal specification 2nd material response

**Surface Treatment:**

Enamel lusterless

**Surface Treatment Specification:**

Tt-e-529 cr 24533 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0