

View Online at <https://aerobasegroup.com/nsn/5340-01-112-1596>

Fabrication Method (non-core):

Welded

First Leg Length:

1.380 inches

Second Leg Length:

1.500 inches

Second Leg Width:

3.250 inches

Second Leg End Width:

2.750 inches

First Leg Slot Length:

0.680 inches

First Leg Slot Width:

0.406 inches

Second Leg Hole Diameter:

Between 0.688 inches and 0.719 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.625 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

3.250 inches

First Leg End Width:

2.750 inches

First Leg Distance Between Hole Centers Along Width:

2.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.535 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second leg hole has keyway 0.186 lg x 0.156 w parallel to width lh

Material:

Aluminum alloy 5086 or aluminum alloy 5083

Material Specification:

Qq-a-250/7 al 5086-h32 federal specification 1st material response or qq-a-250/6 al 5083-h323 federal specification 2nd material response

Surface Treatment:

Enamel lusterless

Surface Treatment Specification:

Tt-e-529 cr 24533 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0