

View Online at <https://aerobasegroup.com/nsn/5340-01-113-2310>

Fabrication Method (non-core):

Extruded

Mounting Hole Type:

Plain

First Leg Length:

0.750 inches

Second Leg Length:

Between 0.750 inches and 0.780 inches

Second Leg Width:

Between 1.480 inches and 1.520 inches

Second Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Hole Diameter:

Between 0.129 inches and 0.134 inches

Second Leg Hole Diameter:

Between 0.263 inches and 0.266 inches

Second Leg Distance Between Hole Centers Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.280 inches

First Leg Thickness:

0.064 inches

Second Leg Thickness:

0.064 inches

First Leg Width:

Between 1.480 inches and 1.520 inches

First Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Distance Between First And Second Hole Centers Along Width:

Between 0.490 inches and 0.510 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.220 inches and 0.280 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.280 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Surface Treatment:

Plastic epoxy

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0