

View Online at <https://aerobasegroup.com/nsn/5340-01-114-0089>

Mounting Hole Type:

Countersunk

First Leg Length:

Between 0.580 inches and 0.620 inches

Second Leg Length:

Between 0.580 inches and 0.620 inches

First Leg Hole Diameter:

0.136 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

Center Section Height:

1.850 inches

Center Section Thickness:

0.050 inches

First Leg Width:

1.620 inches

First Leg End Width:

1.250 inches

First Leg Distance Between Hole Centers Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.560 inches

First Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

0.06 radians

Second Leg Angle:

0.06 radians

First Leg Chamfer Angle:

45.0 degrees

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Tin

Surface Treatment Specification:

Mil-t-10727, type 1 military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-t-10727 spec.