## NSN 5340-01-115-4659

Webbing Strap - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-115-4659
Width:
Between 0.938 inches and 1.062 inches
Length:
162.000 inches
Environmental Protection:
Heat resistant and light resistant
End Type:
Both w/attachments
Ring Material:
Steel, mil-s-6758, comp 4130
Buckle Material:
Steel, aisi 4130 and aluminum alloy, qq-a-250/4, alloy 2024, t3
Buckle Surface Treatment:
Cadmium, qq-p-416, type 2, class 3 and anodized, mil-a-8625 or chromate, mil-c-5541
Buckle Location:
One end
Fastened Buckle Feature:
Included
Buckle Fastening Method:
Sewed
Keeper Material:
Steel, mil-s-6758, comp 4130
Keeper Quantity:
1
Fastened Keeper Feature:
Included
Ring Shape:
D
Fastened Ring Feature:
Included
Ring Fastening Method:
Sewed
Ring Location:
Located on end
End Attachment/fastening Facility:
Ring
Buckle Style Designator:
Tie down
Color:
Olive drab no. 7, fed standard 595 shade 34087
· · ·

Material:

Nylon, mil-w-4088, type 25

## NSN 5340-01-115-4659

Webbing Strap - Page 2 of 2

Mil-std (military Standard):

Mil-w-4088 spec.



Material:
Plastic polyhexamethylene adipamide
Material Specification:
Mil-w-4088, type 25 military specification single material response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T372-b