NSN 5340-01-116-1567

Swivel Caster - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-116-1567

Center To Center Distance Between Bolt Holes Along Width:
Between 6.990 inches and 7.010 inches
Center To Center Distance Between Bolt Holes Along Length:
Between 9.740 inches and 9.760 inches
Wheel Quantity:
1
Safe Operating Load Rating:
950.0 pounds
Material And Location:
Steel wheel rim err-100 err-100 or aluminum alloy wheel rim err-100 err-100
Wheel Type:
Pneumatic tire
Wheel Diameter:
16.000 inches
Effective Height:
20.500 inches
Features Provided:
Brake lock and swivel lock
Plate Style:
Rectangular
Wheel Bearing Type:
Tapered roller
Swivel Bearing Type:
Swivel Bearing Type: Annular ball or roller or tapered roller
Annular ball or roller or tapered roller
Annular ball or roller or tapered roller Swivel Bearing Arrangement:
Annular ball or roller or tapered roller Swivel Bearing Arrangement: Two row
Annular ball or roller or tapered roller Swivel Bearing Arrangement: Two row Tread Width:
Annular ball or roller or tapered roller Swivel Bearing Arrangement: Two row Tread Width: 4.000 inches
Annular ball or roller or tapered roller Swivel Bearing Arrangement: Two row Tread Width: 4.000 inches Caster Plate Length:
Annular ball or roller or tapered roller Swivel Bearing Arrangement: Two row Tread Width: 4.000 inches Caster Plate Length: 11.000 inches
Annular ball or roller or tapered roller Swivel Bearing Arrangement: Two row Tread Width: 4.000 inches Caster Plate Length: 11.000 inches Caster Plate Width:
Annular ball or roller or tapered roller Swivel Bearing Arrangement: Two row Tread Width: 4.000 inches Caster Plate Length: 11.000 inches Caster Plate Width: 9.000 inches
Annular ball or roller or tapered roller Swivel Bearing Arrangement: Two row Tread Width: 4.000 inches Caster Plate Length: 11.000 inches Caster Plate Width: 9.000 inches Caster Plate Mounting Hole Diameter:
Annular ball or roller or tapered roller Swivel Bearing Arrangement: Two row Tread Width: 4.000 inches Caster Plate Length: 11.000 inches Caster Plate Width: 9.000 inches Caster Plate Mounting Hole Diameter: Between 0.652 inches and 0.660 inches
Annular ball or roller or tapered roller Swivel Bearing Arrangement: Two row Tread Width: 4.000 inches Caster Plate Length: 11.000 inches Caster Plate Width: 9.000 inches Caster Plate Mounting Hole Diameter: Between 0.652 inches and 0.660 inches Style Designator:
Annular ball or roller or tapered roller Swivel Bearing Arrangement: Two row Tread Width: 4.000 inches Caster Plate Length: 11.000 inches Caster Plate Width: 9.000 inches Caster Plate Mounting Hole Diameter: Between 0.652 inches and 0.660 inches Style Designator: Swivel offset
Annular ball or roller or tapered roller Swivel Bearing Arrangement: Two row Tread Width: 4.000 inches Caster Plate Length: 11.000 inches Caster Plate Width: 9.000 inches Caster Plate Mounting Hole Diameter: Between 0.652 inches and 0.660 inches Style Designator: Swivel offset Shelf Life:
Annular ball or roller or tapered roller Swivel Bearing Arrangement: Two row Tread Width: 4.000 inches Caster Plate Length: 11.000 inches Caster Plate Width: 9.000 inches Caster Plate Mounting Hole Diameter: Between 0.652 inches and 0.660 inches Style Designator: Swivel offset Shelf Life: N/a

No

NSN 5340-01-116-1567

Swivel Caster - Page 2 of 2



Fiig:

A25600