

View Online at <https://aerobasegroup.com/nsn/5340-01-119-5960>

**First Leg Length:**

Between 0.870 inches and 0.930 inches

**Second Leg Length:**

Between 1.090 inches and 1.150 inches

**Second Leg Width:**

2.030 inches

**Second Leg Corner Radius:**

Between 0.280 inches and 0.340 inches

**First Leg Hole Diameter:**

Between 0.227 inches and 0.233 inches

**Second Leg Hole Diameter:**

Between 0.128 inches and 0.134 inches

**Second Leg Distance Between Lower Hole Centers Along Width:**

Between 1.390 inches and 1.430 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.230 mils and 0.290 centimeters

**Second Leg Distance Between First And Second Hole Centers Along Width:**

Between 0.670 inches and 0.730 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.280 inches and 0.340 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.280 inches and 0.340 inches

**First Leg Thickness:**

0.025 inches

**Second Leg Thickness:**

0.025 inches

**First Leg Width:**

Between 0.970 inches and 1.030 inches

**First Leg Corner Radius:**

Between 0.280 inches and 0.340 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.470 inches and 0.530 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.380 inches and 0.440 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1095

**Material Specification:**

Mil-s-7947 military specification single material response

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

595 color no. 34151 federal standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-s-7947 spec.