

View Online at <https://aerobasegroup.com/nsn/5340-01-121-4614>

**Chamfer Angle In Deg:**

30.0

**Overall Height:**

Between 0.9740 inches and 1.0540 inches

**First Step Diameter:**

Between 0.5970 inches and 0.6070 inches

**First Step Length:**

0.0930 inches

**Second Step Diameter:**

0.9800 inches

**Second Step Length:**

0.0930 inches

**Bore Diameter:**

Between 0.1540 inches and 0.1620 inches

**Second End Diameter:**

Between 0.3030 inches and 0.3080 inches

**Design Type:**

Solid

**End Diameter:**

Between 0.3200 inches and 0.3300 inches

**Distance From End To First Step:**

0.1880 inches

**Special Features:**

Not casehardened

**Material:**

Steel, qq-s-763, class 304, cond a

**Material:**

Steel comp 304

**Material Specification:**

Qq-s-763, class 304, cond a federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ps13001, mcdonnell douglas corporation mfr ref single treatment response

**Style Designator:**

Seat

**Surface Treatment:**

Passivated, ps13001, mcdonnell douglas corp

**Fsc Application Data:**

Cylinder assembly, actuating linear

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T319-e