

View Online at <https://aerobasegroup.com/nsn/5340-01-123-2864>

Mounting Hole Type:

Countersunk

First Leg Length:

0.625 inches

Second Leg Length:

0.688 inches

Second Leg Width:

1.000 inches

Second Leg Corner Radius:

0.188 inches

First Leg Hole Diameter:

Between 0.097 inches and 0.102 inches

Second Leg Hole Diameter:

Between 0.146 inches and 0.152 inches

Second Leg Distance Between Hole Centers Along Width:

0.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.188 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.188 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

1.000 inches

First Leg Corner Radius:

0.188 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.686 inches and 0.690 inches

First Leg Distance From Edge To Hole Center Along Width:

0.156 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/4, t62 federal specification single material response

Surface Treatment:

Primer

Surface Treatment Specification:

Gf14a finish no. 161 fscm 26512 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0