Helical Compression Spring Seat - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-125-0522

Counterbore Diameter:

Between 0.7810 inches and 0.7910 inches

Overall Height:

0.2600 inches

First Step Diameter:

0.8750 inches

Bore Diameter:

Between 0.5050 inches and 0.5090 inches

Ridge Height:

0.0150 inches

Design Type:

Solid

End Diameter:

0.7120 inches

Distance From End To First Step:

Between 0.1340 inches and 0.1440 inches

Counterbore Length:

0.1160 inches

Err Default:

Err default and err default

Distance From Center To Beginning Of Ridge:

0.3560 inches

Special Features:

Not casehardened

Material:

Steel, qq-s-763, class 304, cond a

Material:

Steel comp 304

Material Specification:

Qq-s-763, class 304, cond a federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ps13001, mcdonnell douglas corporation mfr ref single treatment response

Style Designator:

Seat

Surface Treatment:

Passivated, ps13001, mcdonnell douglas corp

Fsc Application Data:

Cylinder assembly, actuating linear, aircraft

Shelf Life:

N/a

Helical Compression Spring Seat - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

Т319-е