

View Online at <https://aerobasegroup.com/nsn/5340-01-125-0585>

**First Leg Length:**

4.000 inches

**Second Leg Length:**

5.620 inches

**End Application:**

NSN2-35-001-0485

**Second Leg Width:**

4.000 inches

**Second Leg End Width:**

2.000 inches

**First Leg Slot Length:**

Between 0.875 inches and 0.938 inches

**First Leg Slot Width:**

Between 0.656 inches and 0.687 inches

**Second Leg Hole Diameter:**

0.500 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.590 inches

**Second Leg Distance Between Hole Centers Along Length:**

2.590 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.080 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.175 inches

**First Leg Thickness:**

0.620 inches

**Second Leg Thickness:**

0.750 inches

**First Leg Width:**

4.750 inches

**First Leg End Width:**

3.750 inches

**First Leg Distance Between Hole Centers Along Width:**

3.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.875 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**First Leg Chamfer Angle:**

50.0 degrees

**Second Leg Chamfer Angle:**

45.0 degrees

**Special Features:**

Fifth hole in second leg 2.585 in. Min 2.595 in. Maximum dia. 4 holes on second leg are threaded 0.500-13 unc-2b; first leg is machined along length per drawing

**Material:**

Steel or steel comp 1020 or steel comp 1030

**Material Specification:**

Qq-s-741 federal specification 1st material response and mil-s-22141 military specification 2nd material response and mjl-s-22141 military specification 3rd material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-s-22141 spec.