

View Online at <https://aerobasegroup.com/nsn/5340-01-125-0586>

First Leg Length:

4.000 inches

Second Leg Length:

5.620 inches

End Application:

NSN2-35-001-0485

Second Leg Width:

4.000 inches

Second Leg End Width:

2.000 inches

First Leg Slot Length:

Between 0.875 inches and 0.938 inches

First Leg Slot Width:

Between 0.656 inches and 0.687 inches

Second Leg Hole Diameter:

0.375 inches

Second Leg Distance Between Hole Centers Along Width:

2.590 inches

Second Leg Distance Between Hole Centers Along Length:

2.590 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.080 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.175 inches

First Leg Thickness:

0.620 inches

Second Leg Thickness:

0.750 inches

First Leg Width:

4.750 inches

First Leg End Width:

3.750 inches

First Leg Distance Between Hole Centers Along Width:

3.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.875 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

50.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

Fifth hole in second leg 2.585 in. Min 2.595 in. Maximum dia. 4 holes on second leg are threaded 0.376-16 unc-2b; first leg is machined along length per drawing

Material:

Steel or steel comp 1020 or steel comp 1030

Material Specification:

Qq-s-741 federal specification 1st material response and mil-s-22141 military specification 2nd material response and mil-s-22141 military specification 3rd material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-22141 spec.