

View Online at <https://aerobasegroup.com/nsn/5340-01-125-0588>

**First Leg Length:**

2.690 inches

**Second Leg Length:**

3.220 inches

**End Application:**

NSN2-35-001-0485

**Second Leg Width:**

2.880 inches

**First Leg Hole Diameter:**

Between 0.313 inches and 0.398 inches

**Second Leg Hole Diameter:**

0.250 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.500 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.062 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.251 inches

**First Leg Thickness:**

0.375 inches

**Second Leg Thickness:**

0.500 inches

**First Leg Width:**

1.690 inches

**First Leg Distance Between Hole Centers Along Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.650 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

First leg, cut out 0.56 in. Radius 0.25 in. Deep; second leg, no surface treatment on outside per drawing, groove cut 0.50 radius per drawing

**Material:**

Aluminum alloy 5083 or aluminum alloy 5086

**Material Specification:**

H321, qq-a-250/6 federal specification 1st material response and h32, qq-a-250/7 federal specification 2nd material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 3, cl 1 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.