

View Online at <https://aerobasegroup.com/nsn/5340-01-125-0588>

First Leg Length:

2.690 inches

Second Leg Length:

3.220 inches

End Application:

NSN2-35-001-0485

Second Leg Width:

2.880 inches

First Leg Hole Diameter:

Between 0.313 inches and 0.398 inches

Second Leg Hole Diameter:

0.250 inches

Second Leg Distance Between Hole Centers Along Width:

1.500 inches

Second Leg Distance Between Hole Centers Along Length:

1.062 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.251 inches

First Leg Thickness:

0.375 inches

Second Leg Thickness:

0.500 inches

First Leg Width:

1.690 inches

First Leg Distance Between Hole Centers Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.650 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First leg, cut out 0.56 in. Radius 0.25 in. Deep; second leg, no surface treatment on outside per drawing, groove cut 0.50 radius per drawing

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

H321, qq-a-250/6 federal specification 1st material response and h32, qq-a-250/7 federal specification 2nd material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 3, cl 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.