
NSN 5340-01-125-1836

Double Angle Bracket - Page 1 of 2





Mounting Hole Type:
Plain
First Leg Length:
0.660 inches
Second Leg Length:
1.400 inches
Second Leg Width:
0.940 inches
First Leg Slot Length:
0.300 inches
First Leg Slot Width:
0.250 inches
Second Leg Hole Diameter:
Between 0.128 inches and 0.134 inches
Second Leg Distance Between Hole Centers Along Width:
0.406 inches
Second Leg Distance Between Hole Centers Along Length:
0.875 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.125 inches
First Leg Thickness:
0.062 inches
Second Leg Thickness:
0.062 inches
Center Section Height:
1.190 inches
Center Section Width:
0.940 inches
Center Section Thickness:
0.062 inches
First Leg Width:
0.940 inches
First Leg Distance From Edge To Hole Center Along Width:
0.250 inches
First Leg Distance From Edge To Hole Center Along Length:
0.250 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
One slot
Second Leg Style:
Square

NSN 5340-01-125-1836

Double Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees Second Leg Angle: 90.0 degrees **Special Features:** One additional slot in first leg, 0.300 in. Lg, 0.156 in. W Material: Steel comp 302 **Material Specification:** Qq-s-766, 1/4 hard federal specification single material response **Surface Treatment:** Passivate Surface Treatment Specification: Mil-f-14072 military specification single treatment response Style Designator: Double angle Shelf Life: N/a Unit Of Measure: ---

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-f-14072 spec.