

View Online at <https://aerobasegroup.com/nsn/5340-01-126-0477>

Fabrication Method (non-core):

Any acceptable

Mounting Hole Type:

Plain

First Leg Length:

2.500 inches

Second Leg Length:

5.500 inches

Reinforcement Method (non-core):

Gusset one side

Second Leg Width:

3.188 inches

First Leg Hole Diameter:

Between 0.279 inches and 0.289 inches

Second Leg Hole Diameter:

Between 0.184 inches and 0.190 inches

Second Leg Distance Between Hole Centers Along Width:

0.312 inches

Second Leg Distance Between Hole Centers Along Length:

4.891 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.531 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.234 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

3.188 inches

First Leg Distance Between Hole Centers Along Width:

2.000 inches

First Leg Distance Between Hole Centers Along Length:

1.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.594 inches

First Leg Distance From Edge To Hole Center Along Length:

0.375 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Four additional 0.187 in. Diameter holes in second leg and a clinch nut attached to each hole in second leg

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-25018, h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.