NSN 5340-01-126-4819

Access Cover - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5540-01-126-4619 |
|---|
| Cross Sectional Shape: |
| Flat |
| Hole Diameter: |
| Between 0.279 inches and 0.288 inches |
| Width: |
| 6.655 inches |
| Edge Shape: |
| Rectangle, four holes |
| Length: |
| Between 7.970 inches and 8.030 inches |
| Distance Between Holes Along Length: |
| 7.250 inches |
| Distance Between Holes Along Width: |
| 5.875 inches |
| Distance From First Hole Centerline To End Along Length: |
| Between 0.345 inches and 0.405 inches |
| Distance From First Hole Centerline To End Along Width: |
| Between 0.345 inches and 0.405 inches |
| Body Thickness: |
| 0.125 inches |
| Mounting Opening Shape Style: |
| Unthreaded hole |
| Features Provided: |
| Special marking |
| Special Features: |
| 10 holes along lengths 0.467 in. Min 0.477 in. Maximum diameter and equally spaced at 1.312 in |
| Material: |
| Aluminum alloy 1100 |
| Material Specification: |
| Qq-a-250/1 h14 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 ty2 cl1 military specification single treatment response and mil-a-8625 ty2 cl2 military specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A531c0 |

NSN 5340-01-126-4819

Access Cover - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.