NSN 5340-01-127-7668

Angle Bracket - Page 1 of 2





First Leg Length:

0.438 inches

Second Leg Length:

1.000 inches

Second Leg Width:

Between 1.344 inches and 1.406 inches

First Leg Hole Diameter:

0.172 inches

Second Leg Hole Diameter:

0.125 inches

Second Leg Distance Between Hole Centers Along Width:

1.062 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.156 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.562 inches

First Leg Thickness:

Between 0.059 inches and 0.067 inches

Second Leg Thickness:

Between 0.059 inches and 0.067 inches

First Leg Width:

Between 1.344 inches and 1.406 inches

First Leg Distance Between Hole Centers Along Width:

1.062 inches

First Leg Distance From Edge To Hole Center Along Width:

0.156 inches

First Leg Distance From Edge To Hole Center Along Length:

0.188 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 5052

NSN 5340-01-127-7668

Angle Bracket - Page 2 of 2



Material Specification: Qq-a-250/8 federal specification single material response Surface Treatment: Chromate Surface Treatment Specification: Mil-c-5541 ty2 cl3 military specification single treatment response Style Designator: Angle Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A042a0 Mil-std (military Standard): Mil-c-5541 spec.