

View Online at <https://aerobasegroup.com/nsn/5340-01-127-8081>

First Leg Length:

0.750 inches

Second Leg Length:

0.750 inches

Second Leg Width:

Between 0.980 inches and 1.020 inches

Second Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Hole Diameter:

Between 0.129 inches and 0.134 inches

Second Leg Hole Diameter:

Between 0.263 inches and 0.266 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.490 inches and 0.510 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.220 inches and 0.280 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.280 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

Between 0.980 inches and 1.020 inches

First Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.220 inches and 0.280 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.280 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Primer color 34151 interior green

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-200/3 t8511 federal specification single material response or qq-a-250/5 t81 federal specification single material response or qq-a-250/5 t72 federal specification single material response

Surface Treatment:

Primer

Surface Treatment Specification:

Mms405 fscm 76301 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0