

View Online at <https://aerobasegroup.com/nsn/5340-01-127-8604>

**First Leg Length:**

Between 0.844 inches and 0.906 inches

**Second Leg Length:**

Between 0.969 inches and 1.031 inches

**Second Leg Width:**

Between 3.980 inches and 4.020 inches

**Second Leg Corner Radius:**

0.125 inches

**First Leg Slot Length:**

Between 0.373 inches and 0.385 inches

**First Leg Slot Width:**

Between 0.170 inches and 0.182 inches

**Second Leg Hole Diameter:**

Between 0.123 inches and 0.135 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 3.490 inches and 3.510 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.230 inches

**First Leg Thickness:**

0.080 inches

**Second Leg Thickness:**

0.080 inches

**First Leg Width:**

Between 3.980 inches and 4.020 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 3.230 inches and 3.270 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.375 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.295 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

First leg also has two holes 0.156 in. Diameter and second leg has additional round hole with 0.375 in. Diameter and slanted slotted hole 0.375 in. By 0.500 in.

**Material:**

Aluminum alloy

**Material Specification:**

Astm b-209, alloy 5005 h34 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0