

View Online at <https://aerobasegroup.com/nsn/5340-01-127-8604>

First Leg Length:

Between 0.844 inches and 0.906 inches

Second Leg Length:

Between 0.969 inches and 1.031 inches

Second Leg Width:

Between 3.980 inches and 4.020 inches

Second Leg Corner Radius:

0.125 inches

First Leg Slot Length:

Between 0.373 inches and 0.385 inches

First Leg Slot Width:

Between 0.170 inches and 0.182 inches

Second Leg Hole Diameter:

Between 0.123 inches and 0.135 inches

Second Leg Distance Between Hole Centers Along Width:

Between 3.490 inches and 3.510 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.230 inches

First Leg Thickness:

0.080 inches

Second Leg Thickness:

0.080 inches

First Leg Width:

Between 3.980 inches and 4.020 inches

First Leg Distance Between Hole Centers Along Width:

Between 3.230 inches and 3.270 inches

First Leg Distance From Edge To Hole Center Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Length:

0.295 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First leg also has two holes 0.156 in. Diameter and second leg has additional round hole with 0.375 in. Diameter and slanted slotted hole 0.375 in. By 0.500 in.

Material:

Aluminum alloy

Material Specification:

Astm b-209, alloy 5005 h34 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0