

View Online at <https://aerobasegroup.com/nsn/5340-01-128-5218>

First Leg Length:

0.430 inches

Second Leg Length:

0.550 inches

Second Leg Width:

1.500 inches

First Leg Hole Diameter:

Between 0.125 inches and 0.131 inches

Second Leg Hole Diameter:

Between 0.191 inches and 0.197 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.400 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

0.400 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.150 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.181 inches

First Leg Thickness:

Between 0.0458 inches and 0.0558 inches

Second Leg Thickness:

Between 0.0458 inches and 0.0558 inches

First Leg Width:

1.500 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.795 inches and 0.805 inches

First Leg Distance From Edge To Hole Center Along Width:

0.200 inches

First Leg Distance From Edge To Hole Center Along Length:

0.189 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second leg having four holes 0.191 in. Min dia, 0.197 in. Maximum dia, with one end flat

Material:

Copper alloy 260 or copper alloy 268

Material Specification:

Qq-b-613, temper 1/2 hard federal specification all material responses

Surface Treatment:

Tin

Surface Treatment Specification:

580-0151-000 fscm 13499 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0