

View Online at <https://aerobasegroup.com/nsn/5340-01-129-3092>

First Leg Length:

Between 1.220 inches and 1.280 inches

Second Leg Length:

Between 1.030 inches and 1.090 inches

Second Leg Width:

Between 0.970 inches and 1.030 inches

First Leg Slot Length:

Between 0.620 inches and 0.650 inches

First Leg Slot Width:

Between 0.280 inches and 0.300 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.470 inches and 0.530 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.350 inches and 0.410 inches

Second Leg Slot Length:

Between 0.500 inches and 0.530 inches

Second Leg Slot Width:

Between 0.280 inches and 0.300 inches

First Leg Thickness:

0.1196 inches

Second Leg Thickness:

0.1196 inches

First Leg Width:

0.760 inches

First Leg End Width:

Between 0.970 inches and 1.030 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.470 inches and 0.530 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.590 inches and 0.650 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel

Material Specification:

Qq-s-698, no. 11 msga federal specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0