

View Online at <https://aerobasegroup.com/nsn/5340-01-129-8517>

Countersink Angle In Deg:

45.0

Chamfer Angle In Deg:

15.0

Counterbore Diameter:

Between 0.5000 inches and 0.5050 inches

Overall Height:

0.7410 inches

First Step Diameter:

Between 0.5550 inches and 0.5600 inches

First Step Length:

0.6030 inches

Second Step Diameter:

0.6870 inches

Bore Diameter:

0.0930 inches

Material Hardness Rating:

Between 24.0 rockwell c and 32.0 rockwell c

Design Type:

Solid

Countersink Diameter:

Between 0.6000 inches and 0.6050 inches

End Diameter:

Between 0.5230 inches and 0.5280 inches

Distance From End To First Step:

0.0600 inches

Counterbore Length:

Between 0.5600 inches and 0.5700 inches

Special Features:

Not casehardened

Material:

Steel, astm a582, type 416

Material:

Steel comp 416

Material Specification:

Astm a582, type 416 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ps13001, mcdonnell douglas corporation mfr ref single treatment response

Style Designator:

Seat

Surface Treatment:

Passivated, ps13001, mcdonnell douglas corp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T319-e