

View Online at <https://aerobasegroup.com/nsn/5340-01-129-8517>

**Countersink Angle In Deg:**

45.0

**Chamfer Angle In Deg:**

15.0

**Counterbore Diameter:**

Between 0.5000 inches and 0.5050 inches

**Overall Height:**

0.7410 inches

**First Step Diameter:**

Between 0.5550 inches and 0.5600 inches

**First Step Length:**

0.6030 inches

**Second Step Diameter:**

0.6870 inches

**Bore Diameter:**

0.0930 inches

**Material Hardness Rating:**

Between 24.0 rockwell c and 32.0 rockwell c

**Design Type:**

Solid

**Countersink Diameter:**

Between 0.6000 inches and 0.6050 inches

**End Diameter:**

Between 0.5230 inches and 0.5280 inches

**Distance From End To First Step:**

0.0600 inches

**Counterbore Length:**

Between 0.5600 inches and 0.5700 inches

**Special Features:**

Not casehardened

**Material:**

Steel, astm a582, type 416

**Material:**

Steel comp 416

**Material Specification:**

Astm a582, type 416 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ps13001, mcdonnell douglas corporation mfr ref single treatment response

**Style Designator:**

Seat

**Surface Treatment:**

Passivated, ps13001, mcdonnell douglas corp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T319-e