

View Online at <https://aerobasegroup.com/nsn/5340-01-131-9513>

First Leg Length:

0.750 inches

Second Leg Length:

0.800 inches

Second Leg Width:

1.000 inches

Second Leg Corner Radius:

0.300 inches

First Leg Hole Diameter:

Between 0.129 inches and 0.134 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.300 inches

Second Leg Slot Length:

0.499 inches

Second Leg Slot Width:

0.224 inches

First Leg Thickness:

0.071 inches

Second Leg Thickness:

0.071 inches

First Leg Width:

1.188 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One slot

Criticality Code Justification:

Feat

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

For conventional installation

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5 t72 federal specification single material response or qq-a-250/5 t81 federal specification single material response

Surface Treatment:

Primer

Surface Treatment Specification:

Mms425 fscm 76301 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0