

View Online at <https://aerobasegroup.com/nsn/5340-01-132-3465>

**First Leg Length:**

Between 0.890 inches and 0.920 inches

**Second Leg Length:**

Between 0.988 inches and 1.010 inches

**Second Leg Width:**

Between 0.690 inches and 0.710 inches

**First Leg Hole Diameter:**

Between 0.155 inches and 0.160 inches

**Second Leg Hole Diameter:**

Between 0.342 inches and 0.350 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.340 inches and 0.360 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.340 inches and 0.350 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

Between 0.690 inches and 0.710 inches

**First Leg Distance Between Hole Centers Along Length:**

0.400 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.340 inches and 0.360 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.190 inches and 0.210 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Two self clinching round nuts per mil-n-45938 on holes inner face of first leg

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11, t4 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-c-5541, cl 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.