

View Online at <https://aerobasegroup.com/nsn/5340-01-132-3465>

First Leg Length:

Between 0.890 inches and 0.920 inches

Second Leg Length:

Between 0.988 inches and 1.010 inches

Second Leg Width:

Between 0.690 inches and 0.710 inches

First Leg Hole Diameter:

Between 0.155 inches and 0.160 inches

Second Leg Hole Diameter:

Between 0.342 inches and 0.350 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.340 inches and 0.360 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.340 inches and 0.350 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

Between 0.690 inches and 0.710 inches

First Leg Distance Between Hole Centers Along Length:

0.400 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.340 inches and 0.360 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.190 inches and 0.210 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Two self clinching round nuts per mil-n-45938 on holes inner face of first leg

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.