

View Online at <https://aerobasegroup.com/nsn/5340-01-135-9348>

Fabrication Method (non-core):

Any acceptable

Mounting Hole Type:

Plain

First Leg Length:

2.400 inches

Second Leg Length:

2.870 inches

Reinforcement Method (non-core):

Gusset both sides

Second Leg Width:

4.360 inches

First Leg Hole Diameter:

0.500 inches

Second Leg Hole Diameter:

Between 0.208 inches and 0.228 inches

Second Leg Distance Between Hole Centers Along Width:

2.125 inches

Second Leg Distance Between Hole Centers Along Length:

2.125 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.372 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

4.360 inches

First Leg Distance Between Upper Hole Centers Along Width:

3.250 inches

First Leg Distance Between Hole Centers Along Length:

1.312 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.625 inches

First Leg Distance From Edge To Hole Center Along Width:

0.555 inches

First Leg Distance From Edge To Hole Center Along Length:

0.400 inches

First Leg End Radius:

0.400 inches

First Leg Style:

End radius and tapered

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 304l or steel comp 347

Material Specification:

Ams 5510 assn standard 1st material response or ams 5512 assn standard 2nd material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0