

View Online at <https://aerobasegroup.com/nsn/5340-01-139-6812>

Mounting Hole Type:

Counterbored

First Leg Length:

Between 0.850 inches and 0.910 inches

Second Leg Length:

Between 0.880 inches and 0.920 inches

Second Leg Width:

1.850 inches

Second Leg Corner Radius:

0.250 inches

First Leg Hole Diameter:

Between 0.280 inches and 0.285 inches

Second Leg Hole Diameter:

Between 0.330 inches and 0.340 inches

Second Leg Distance Between Hole Centers Along Width:

Between 1.000 inches and 1.010 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

Between 0.068 inches and 0.074 inches

Second Leg Thickness:

Between 0.068 inches and 0.074 inches

First Leg Width:

Between 1.230 inches and 1.270 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.870 inches and 0.890 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.340 inches and 0.360 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

1st leg hole counterbored, 0.375 in. Min and 0.395 in. Maximum dia, 0.025 in. Min and 0.035 in. Maximum dp; 2nd leg comes with two bolts

Material:

Stainless steel

Material Specification:

Ams5599 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0