

View Online at <https://aerobasegroup.com/nsn/5340-01-139-9992>

First Leg Length:

0.460 inches

Second Leg Length:

0.570 inches

Second Leg Width:

0.840 inches

First Leg Hole Diameter:

0.140 inches

Second Leg Hole Diameter:

0.096 inches

Second Leg Distance Between Hole Centers Along Width:

0.640 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.100 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.150 inches

First Leg Thickness:

0.053 inches

Second Leg Thickness:

0.053 inches

First Leg Width:

0.840 inches

First Leg Distance Between Hole Centers Along Width:

0.420 inches

First Leg Distance From Edge To Hole Center Along Width:

0.210 inches

First Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

2nd leg has cut-out 0.440 in. Lg by 0.385 in. Dp; bracket, bearing

Material:

Aluminum alloy

Material Specification:

Qq-a-250/11 temp t4 federal specification single material response

Surface Treatment:

Passivate and primer and enamel

Surface Treatment Specification:

Mil-f-14072, e12 military specification 1st treatment response and mil-p-23377 military specification 2nd treatment response and mil-p-22808 med gray military specification 3rd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-f-14072 spec.