NSN 5340-01-140-4681

Angle Bracket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-140-4681

First Leg Thickness: 0.090 inches Second Leg Thickness: 0.090 inches First Leg Angle: 90.0 degrees Special Features: First leg has 15 holes: 6 holes, 0.130 in. Dia; 8 holes, 0.1175 in. Dia; 1 hole, 0.146 in. Dia; second leg has 6 holes: 4 holes, 0.225 in 2 holes, 0.175 in. Dia; first leg furnished with nutplate, 2.240 in. Lg; 0.700 in. W; with 2 nuts; center-to-center distance between nuts in.; each nut mounting hole 0.214 in. Dia Material: Aluminum alloy 6061 Material Specification:	
Second Leg Thickness: 0.090 inches First Leg Angle: 90.0 degrees Special Features: First leg has 15 holes: 6 holes, 0.130 in. Dia; 8 holes, 0.1175 in. Dia; 1 hole, 0.146 in. Dia; second leg has 6 holes: 4 holes, 0.225 in. 2 holes, 0.175 in. Dia; first leg furnished with nutplate, 2.240 in. Lg; 0.700 in. W; with 2 nuts; center-to-center distance between nuts in.; each nut mounting hole 0.214 in. Dia Material: Aluminum alloy 6061	
0.090 inches First Leg Angle: 90.0 degrees Special Features: First leg has 15 holes: 6 holes, 0.130 in. Dia; 8 holes, 0.1175 in. Dia; 1 hole, 0.146 in. Dia; second leg has 6 holes: 4 holes, 0.225 in. 2 holes, 0.175 in. Dia; first leg furnished with nutplate, 2.240 in. Lg; 0.700 in. W; with 2 nuts; center-to-center distance between nuts in.; each nut mounting hole 0.214 in. Dia Material: Aluminum alloy 6061	
First Leg Angle: 90.0 degrees Special Features: First leg has 15 holes: 6 holes, 0.130 in. Dia; 8 holes, 0.1175 in. Dia; 1 hole, 0.146 in. Dia; second leg has 6 holes: 4 holes, 0.225 in. 2 holes, 0.175 in. Dia; first leg furnished with nutplate, 2.240 in. Lg; 0.700 in. W; with 2 nuts; center-to-center distance between nuts in.; each nut mounting hole 0.214 in. Dia Material: Aluminum alloy 6061	
90.0 degrees Special Features: First leg has 15 holes: 6 holes, 0.130 in. Dia; 8 holes, 0.1175 in. Dia; 1 hole, 0.146 in. Dia; second leg has 6 holes: 4 holes, 0.225 in. 2 holes, 0.175 in. Dia; first leg furnished with nutplate, 2.240 in. Lg; 0.700 in. W; with 2 nuts; center-to-center distance between nuts in.; each nut mounting hole 0.214 in. Dia Material: Aluminum alloy 6061	
Special Features: First leg has 15 holes: 6 holes, 0.130 in. Dia; 8 holes, 0.1175 in. Dia; 1 hole, 0.146 in. Dia; second leg has 6 holes: 4 holes, 0.225 in. 2 holes, 0.175 in. Dia; first leg furnished with nutplate, 2.240 in. Lg; 0.700 in. W; with 2 nuts; center-to-center distance between nuts in.; each nut mounting hole 0.214 in. Dia Material: Aluminum alloy 6061	
First leg has 15 holes: 6 holes, 0.130 in. Dia; 8 holes, 0.1175 in. Dia; 1 hole, 0.146 in. Dia; second leg has 6 holes: 4 holes, 0.225 in. 2 holes, 0.175 in. Dia; first leg furnished with nutplate, 2.240 in. Lg; 0.700 in. W; with 2 nuts; center-to-center distance between nuts in.; each nut mounting hole 0.214 in. Dia Material: Aluminum alloy 6061	
2 holes, 0.175 in. Dia; first leg furnished with nutplate, 2.240 in. Lg; 0.700 in. W; with 2 nuts; center-to-center distance between nuts in.; each nut mounting hole 0.214 in. Dia Material: Aluminum alloy 6061	
in.; each nut mounting hole 0.214 in. Dia Material: Aluminum alloy 6061	1.240
Material: Aluminum alloy 6061	
Aluminum alloy 6061	
Material Specification:	
Qq-a-250/11 federal specification single material response	
Surface Treatment:	
Chromate	
Surface Treatment Specification:	
Mil-c-5541, cl 3 military specification single treatment response	
Style Designator:	
Angle	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A042a0	
Mil-std (military Standard):	
Mil-c-5541 spec.	