

View Online at <https://aerobasegroup.com/nsn/5340-01-143-9557>

Mounting Hole Type:

Threaded

First Leg Length:

0.500 inches

Second Leg Length:

1.440 inches

Second Leg Width:

0.620 inches

Second Leg End Width:

0.500 inches

First Leg Hole Diameter:

0.150 inches

Second Leg Hole Diameter:

0.150 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.302 inches and 0.322 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.150 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.650 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

0.620 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.302 inches and 0.322 inches

First Leg Distance Between Hole Centers Along Length:

Between 0.146 inches and 0.166 inches

First Leg Distance From Edge To Hole Center Along Width:

0.150 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.124 inches and 0.144 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Color black

Material:

Aluminum alloy 356.0

Material Specification:

Qq-a-601, alloy 356-t6 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, class 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.