NSN 5340-01-144-9416

Angle Bracket - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5340-01-144-9416



Plain First Leg Length: 0.620 inches Second Leg Length: 1.460 inches Second Leg Width: 1.000 inches First Leg Hole Diameter: Between 0.126 inches and 0.133 inches
0.620 inches Second Leg Length: 1.460 inches Second Leg Width: 1.000 inches First Leg Hole Diameter:
Second Leg Length: 1.460 inches Second Leg Width: 1.000 inches First Leg Hole Diameter:
1.460 inches Second Leg Width: 1.000 inches First Leg Hole Diameter:
Second Leg Width: 1.000 inches First Leg Hole Diameter:
1.000 inches First Leg Hole Diameter:
First Leg Hole Diameter:
-
Between 0.126 inches and 0.133 inches
Second Leg Hole Diameter:
Between 0.249 inches and 0.255 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.960 inches
First Leg Thickness:
Between 0.036 inches and 0.044 inches
Second Leg Thickness:
Between 0.036 inches and 0.044 inches
First Leg Width:
1.000 inches
First Leg Distance Between Hole Centers Along Width:
0.370 inches
First Leg Distance From Edge To Hole Center Along Width:
0.310 inches
First Leg Distance From Edge To Hole Center Along Length:
0.250 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
One hole
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
0.12 radians
Material:
Aluminum alloy 2024

NSN 5340-01-144-9416

Angle Bracket - Page 2 of 2



Material Specification:

Qq-a-250/5, temp t3 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-std-171 military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.