

View Online at <https://aerobasegroup.com/nsn/5340-01-146-6574>

**First Leg Length:**

5.000 inches

**Second Leg Length:**

6.250 inches

**End Application:**

2815-01-086-1402 and 2815-01-127-6841 manifold assemblies, exhaust risers on cummins model vt903m diesel engines onboard 41 foot cg vessels

**Second Leg Width:**

7.500 inches

**First Leg Slot Length:**

0.750 inches

**First Leg Slot Width:**

0.625 inches

**Second Leg Distance Between Hole Centers Along Width:**

6.000 inches

**Second Leg Distance Between Hole Centers Along Length:**

4.375 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.875 inches

**Second Leg Slot Length:**

1.000 inches

**Second Leg Slot Width:**

0.500 inches

**First Leg Thickness:**

0.500 inches

**Second Leg Thickness:**

0.375 inches

**First Leg Width:**

13.000 inches

**First Leg Distance Between Hole Centers Along Width:**

7.250 inches

**First Leg Distance Between Hole Centers Along Length:**

2.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.125 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**First Leg Style:**

Cut out

**First Leg Hole Arrangement Style:**

4 slots

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

4 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**First Leg Cutout Length:**

3.500 inches

**First Leg Cutout Width:**

3.875 inches

**Special Features:**

Gfirst leg has 2 each 1/2 - 13 threaded holes located 1.000 inch from right edge having a 2.500 inch center distance. Second leg has 1 each 1.125 inch o.D.X2.625 inches long round stock welded to back

**Material:**

Steel

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0