

View Online at <https://aerobasegroup.com/nsn/5340-01-146-6574>

First Leg Length:

5.000 inches

Second Leg Length:

6.250 inches

End Application:

2815-01-086-1402 and 2815-01-127-6841 manifold assemblies, exhaust risers on cummins model vt903m diesel engines onboard 41 foot cg vessels

Second Leg Width:

7.500 inches

First Leg Slot Length:

0.750 inches

First Leg Slot Width:

0.625 inches

Second Leg Distance Between Hole Centers Along Width:

6.000 inches

Second Leg Distance Between Hole Centers Along Length:

4.375 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.875 inches

Second Leg Slot Length:

1.000 inches

Second Leg Slot Width:

0.500 inches

First Leg Thickness:

0.500 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

13.000 inches

First Leg Distance Between Hole Centers Along Width:

7.250 inches

First Leg Distance Between Hole Centers Along Length:

2.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.125 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

4 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

4 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Cutout Length:

3.500 inches

First Leg Cutout Width:

3.875 inches

Special Features:

Gfirst leg has 2 each 1/2 - 13 threaded holes located 1.000 inch from right edge having a 2.500 inch center distance. Second leg has 1 each 1.125 inch o.D.X2.625 inches long round stock welded to back

Material:

Steel

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0