

View Online at <https://aerobasegroup.com/nsn/5340-01-147-4098>

Mounting Hole Type:

Counterbored and plain

First Leg Length:

2.410 inches

Second Leg Length:

2.520 inches

Second Leg Width:

2.110 inches

First Leg Hole Diameter:

Between 0.212 inches and 0.219 inches

Second Leg Hole Diameter:

Between 0.280 inches and 0.285 inches

Second Leg Distance Between Hole Centers Along Length:

1.795 mils and 1.805 centimeters

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.320 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.320 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

2.110 inches

First Leg Distance Between Hole Centers Along Width:

Between 1.075 inches and 1.085 inches

First Leg Distance Between Hole Centers Along Length:

Between 1.615 inches and 1.625 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.220 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.260 inches

First Leg End Radius:

Between 0.220 inches and 0.260 inches

Second Leg End Radius:

Between 0.280 inches and 0.320 inches

First Leg Style:

End radius and tapered

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

Two holes

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0