## NSN 5340-01-148-6447

Access Cover - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-148-6447

| End | Δn | nlic | atio | n·  |
|-----|----|------|------|-----|
| ⊏nu | Αþ | piic | auo  | 11. |

Mhu-196/204/m

## **Special Features:**

Material steel, passivated finish; 16 holes along w; 0.120 in. Nom corner radius; 16 holes along lg; 3 in. Nom distance between holes along lg; 1.094 in. Nom distance between hole ctrline and 1st hole along lg; 1.375 in. Nom distance from 1st hole ctrline to end along lg; 1.094 in. Nom distance between hole ctrline and end along w; 1.375 in. Nom distance from 1st hole ctrline to end along w; 3 in. Nom distance between holes along w; 23.750 in. Nom w; 23.750 in. Nom lg; 0.190 in. Nom body thk; 0.187 in. Nom flane thk; thd fasterner type securingk observation facility provided; nomenclature cover, acces

| Mate   | ! !   |   |
|--------|-------|---|
| IVIATE | rıaı  | • |
| mucc   | ı ıaı |   |

Steel

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

Yes - demil/mli

Fiig:

A531c0