

View Online at <https://aerobasegroup.com/nsn/5340-01-148-6824>

Mounting Hole Type:

Plain

First Leg Length:

1.120 inches

Second Leg Length:

1.680 inches

Second Leg Width:

2.500 inches

First Leg Hole Diameter:

Between 0.280 inches and 0.310 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.620 inches

Second Leg Slot Length:

0.750 inches

Second Leg Slot Width:

Between 0.280 inches and 0.310 inches

First Leg Thickness:

0.1196 inches

Second Leg Thickness:

0.1196 inches

First Leg Width:

2.500 inches

First Leg Distance Between Hole Centers Along Width:

1.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.380 inches

First Leg Distance From Edge To Hole Center Along Length:

0.370 inches

Second Leg End Radius:

0.620 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020

Surface Treatment:

Enamel

Surface Treatment Specification:

Tt-e-485 federal specification single treatment response and tt-e-529 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0