# NSN 5340-01-150-2394

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-150-2394

ret	Lea	I An	ath:
 J D L	LCU	LCII	uu.

Between 0.975 inches and 0.995 inches

#### First Leg Hole Diameter:

Between 0.280 inches and 0.285 inches

#### Second Leg Hole Diameter:

Between 0.204 inches and 0.215 inches

#### Second Leg Distance Between Hole Centers Along Width:

1.002 inches

## Second Leg Distance Between Hole Centers Along Length:

0.147 inches

#### First Leg Thickness:

Between 0.057 inches and 0.069 inches

#### Second Leg Thickness:

Between 0.057 inches and 0.069 inches

#### First Leg Width:

Between 0.490 inches and 0.510 inches

#### First Leg Distance From Edge To Hole Center Along Width:

Between 0.245 inches and 0.255 inches

# First Leg Distance From Edge To Hole Center Along Length:

Between 0.350 inches and 0.370 inches

# First Leg End Radius:

Between 0.490 inches and 0.510 inches

# First Leg Style:

End radius

#### First Leg Hole Arrangement Style:

One hole

# Second Leg Hole Arrangement Style:

Two holes

#### Second Leg Relationship To First Leg:

Not identical

### First Leg Angle:

90.0 degrees

### Material:

Stainless steel

#### **Material Specification:**

Ams 5510 assn standard single material response

### Style Designator:

Angle

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5340-01-150-2394

Angle Bracket - Page 2 of 2



Demilitarization:

No

Fiig:

A042a0