

View Online at <https://aerobasegroup.com/nsn/5340-01-150-7198>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.650 inches

**Second Leg Length:**

1.350 inches

**End Application:**

Shear pin plate-trailing edge fairing, inboard and outboard strut

**Second Leg Width:**

1.700 inches

**First Leg Slot Length:**

0.720 inches

**First Leg Slot Width:**

Between 0.2006 inches and 0.2066 inches

**Second Leg Hole Diameter:**

Between 0.199 inches and 0.204 inches

**Second Leg Distance Between Upper Hole Centers Along Width:**

1.100 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.520 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

0.550 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.300 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.310 inches

**First Leg Thickness:**

0.100 inches

**Second Leg Thickness:**

0.100 inches

**First Leg Width:**

1.700 inches

**First Leg End Width:**

0.780 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.850 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.290 inches

**Second Leg End Radius:**

0.310 inches

**First Leg Style:**

Square and tapered

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

2nd leg end chamfered 45 degrees by 0.100

**Material:**

Steel comp 416

**Material Specification:**

Aisi 416 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0