

View Online at <https://aerobasegroup.com/nsn/5340-01-150-7198>

Mounting Hole Type:

Plain

First Leg Length:

0.650 inches

Second Leg Length:

1.350 inches

End Application:

Shear pin plate-trailing edge fairing, inboard and outboard strut

Second Leg Width:

1.700 inches

First Leg Slot Length:

0.720 inches

First Leg Slot Width:

Between 0.2006 inches and 0.2066 inches

Second Leg Hole Diameter:

Between 0.199 inches and 0.204 inches

Second Leg Distance Between Upper Hole Centers Along Width:

1.100 inches

Second Leg Distance Between Hole Centers Along Length:

0.520 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.550 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.300 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Thickness:

0.100 inches

Second Leg Thickness:

0.100 inches

First Leg Width:

1.700 inches

First Leg End Width:

0.780 inches

First Leg Distance From Edge To Hole Center Along Width:

0.850 inches

First Leg Distance From Edge To Hole Center Along Length:

0.290 inches

Second Leg End Radius:

0.310 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

2nd leg end chamfered 45 degrees by 0.100

Material:

Steel comp 416

Material Specification:

Aisi 416 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0